

- THIS ARRANGEMENT IS INTENDED FOR RURAL LOW DENSITY RESIDENTIAL ACCESS WAYS.
- COUNCIL RESERVES THE RIGHT TO DIRECT THE
- VARIATIONS MAY OCCUR AFTER INSPECTION AND APPROVAL OF LOCATION BY COUNCIL.
- PRIOR TO THE CONSTRUCTION, THE CROSSING LOCATION SHALL BE APPROVED BY COUNCIL.
- 5. ALL WORKS TO BE COMPLETED TO THE SATISFACTION OF COUNCIL
- MAINTENANCE OF THE CROSSOVER REMAINS THE RESPONSIBILITY OF THE LAND OWNER.
- DRIVEABLE ENDWALLS TO BE USED WITHIN 1.5m OF THE EDGE OF SEAL
- TABLE DRAINS ARE NOT TO BE CLOSER THAN 1.0m FROM FENCE LINES OR SERVICES.
- CULVERT TO BE LOCATED AT LEAST 600mm FROM EDGE OF SEAL

TYPICAL SWALE DRAIN VEHICLE CROSSING

50 THICK CLASS 3 FINE CRUSHED

ROCK BEDDING LAYER

ALL MEASUREMENTS IN MILLIMETRES

(FRINGE URBAN RESIDENTIAL ENTRANCE)

SECTION A-A

Infrastructure Design Manual Standard Drawings

FINE CRUSHED ROCK BACK FILL FOR

R.C.P. UNDER VEHICLE CROSSING.

Local Government Infrastructure Design Association A copy of the Infrastructure Design Manual can be viewed on the Design Manual website www.designmanual.com.au

LAST UPDATED 06/02/2019

NOT TO SCALE